

## DIAGNOSTICS, INSPECTION & LOCATING

# Reels & Cameras

**NEW**



### SeeSnake® Mini Video Standard & Self-Leveling Inspection Systems

The SeeSnake Mini video inspection system offers unmatched reliability and performance in a ruggedized package. The Mini is now also available with a durable self-leveling camera head.

- 1½" to 6" (3.8 to 15 cm) Lines up to 200' (61 m).
- Ideal for where portability and maneuverability are crucial: multi-story buildings, rooftops, confined areas, etc.
- New Self-Leveling Camera Head – delivers crisp, clear, always upright in-pipe images.
- Built-In 512 Hz Sonde – allows you to locate a point of interest during a pipe inspection.
- Metal Frame and Rugged Drum – stands up to the rigors of a variety of demanding jobsites.
- Push Cable – pushes farther; tackles a wide range of lateral and mainline applications.

### Specifications

- Line Capacity – 1½" to 6" (3.8 to 15 cm).
- Maximum Run – 200' / 61 m.
- Sonde – 512 Hz.
- Weight (Excl Monitor) – 24.5 lbs / 11,1 kg.
- Reel Frame Diameter – 20" / 51 cm.
- Camera Diameter – 1.18" / 30 mm.
- Camera Length – 1.68" / 42 mm.
- Push Cable Diameter – .31" / 8 mm.
- Operating Temperature – -4° to 104°F / -20° to 40°C.
- Waterproof Depth – 330' / 100 m.
- Video Resolution – 768(H) x 494(V).
- Number of Pixels – 410K.
- Lighting – 6 LEDs / 18 LEDs (for self-leveling model).

Catalog No.	Description	Voltage		Weight	
		V	lb.	kg	
14063	200' Mini Color Reel (NTSC)	115	24.5	11.1	
48488	200' Color Self-Leveling Reel (NTSC)	115	24.5	11.1	

### Accessories

Catalog No.	Description	Weight	
		lb.	kg
15828	Mini-SeeSnake Flexmitter	1.0	0.0
17558	Color Spanner Wrench	0.2	0.1
31753	Count Plus Cable Counter	—	—
67307	SeeSnake Interconnect Cord 33/10' (10 m/3 m)	1.1	0.5
67312	101 mm Star Guide, Fits 30 mm Camera (pkg. of 20)	0.7	0.3
93392	Mini Guide Hoop, Pkg of 4	0.2	0.1
97462	60 mm Pipe Guide, Fits 30 mm Camera (pkg. of 6)	0.4	0.2

### Replacement Parts

Catalog No.	Description
12248	18" System Cable with Dubbing Block
14083	Color Camera Head - NTSC (115V)
67322	100' (30 m) Mini SeeSnake Push Cable Assembly
67327	200' (61 m) SeeSnake Push Cable Assembly
48533	Color Self-Leveling Camera Head (NTSC)

## DIAGNOSTICS, INSPECTION & LOCATING

### Reels & Cameras



#### SeeSnake® Standard & Self-Leveling Cameras

RIDGID® SeeSnake video inspection systems offer unmatched reliability and performance in a ruggedized package. Each system offers.

- 100% hardened stainless steel camera head spring assembly for optimum durability.
- Rugged, high-intensity lights for exceptional viewing and long life.
- Flexible transmitters make locating easy and are compatible with RIDGID locators.
- Can be used with any SeeSnake monitor or recorder.
- 2" to 12" (5 - 30 cm) Lines up to 325' (99 m).
- Wide pipe diameter capacity range makes this system ideal for a wide range of inspection needs.

#### Specifications

- Line Capacity – 2" - 12" (5-30cm).
- Maximum Run – 325' (99m).
- Sonde – 512 Hz.
- Weight – 53 lbs / 19.5 kg.
- Reel Frame Diameter – 32" / 81 cm.
- Camera Diameter – 1.365" / 35 mm.
- Camera Length – 1.68" / 42 mm.
- Push Cable Diameter – .44" / 11 mm.
- Operating Temperature – -4° to 104°F / -20° to 40°C.
- Waterproof Depth – 330' / 100 m.
- Video Resolution – 768(H) x 494(V).

Catalog No.	Description	Voltage	Weight	
		V	lb.	kg
14053	200' Color Reel (NTSC)	115	42.0	19.0
14058	325' Color Reel (NTSC)	115	53.0	24.0
13988	200' Self-Leveling Color Reel (NTSC)	115	42.0	19.0
13998	325' Self-Leveling Color Reel (NTSC)	115	53.0	24.0

#### Accessories

Catalog No.	Description	Weight	
		lb.	kg
15323	SeeSnake Flexible In-Line Transmitter	0.6	0.3
17563	Color Spanner Wrench	–	–
31753	Count Plus Cable Counter	–	–
64497	75 mm Star Guide, Fits 35 mm Camera (pkg. of 20)	–	–
64502	150 mm Star Guide, Fits 35 mm Camera (pkg. of 10)	–	–
64627	SeeSnake Interconnect Cord – 33/10' (10 m / 3m)"	–	–
93387	SeeSnake Guide Hoop, Pkg of 4	–	–
97832	SeeSnake 3" (75 mm) Roller Dolly	–	–
97852	85 mm Pipe Guide, Fits 35 mm Camera (pkg. of 10)	–	–

#### Replacement Parts

Catalog No.	Description
12248	18" System Cable with Dubbing Block
14078	Color Camera Head – NTSC (115V)
14128	Color Camera Head – PAL (230V)
35103	200' SeeSnake Push Cable Assembly (Single Safety Cable)
35108	325' SeeSnake Push Cable Assembly (Single Safety Cable)
64607	200' (61 m) SeeSnake Push Cable Assembly
64612	325' (99m) Standard SeeSnake Push Cable Assembly
48543	Color Self-Leveling Camera Head – NTSC (115V)